



## *POWER HAWK*<sup>®</sup> P-16 Rescue System

Extremely powerful and uniquely versatile, the Power Hawk Rescue System is unlike any other rescue tool in the world. This All-Electric (no hydraulics) "jaws" type rescue tool utilizes Curtiss-Wright aerospace gear technology developed for demanding military fighter-jet flight control applications. By eliminating hydraulics completely and utilizing 12 Volts DC power, the VERSATILITY of the POWER HAWK makes it the perfect choice for:

- Vehicle extrication • Crash & Salvage • Damage Control • Rapid-Intervention Teams
- Collapse rescues • Remote rescues • Indoor and confined space operations • Forcible entry
- Special operations and more.

### *Accessory Kits...*

## **Model FAN8-25-1B VENTILATING FAN KIT, 12VDC**



Tough, durable and versatile ...Combines the weather, chemical and dent resistance of a double-wall, polyethylene shell with a high performance, polypropylene fan blade. Detachable in seconds, the Kwik-coupler canister conveniently reverses from the discharge to the suction, making use and storage easier while protecting the duct from rips and tears. For manholes, tanks, cableways, vaults, or other confined spaces, this kit provides the means to safely and efficiently ventilate.

### **Model FAN8-25-1B Kit includes:**

- Model FAN8-12V Portable Ventilating Fan, 12 VDC
- Model FAN-7004CL Canister Duct, 25 Ft.
- Model PWR-3X12 Power Pack, 12V
- Model BC-U1 Battery Charger
- Model EC4-16 Extension Cables, 16 Ft.
- Model JC4-16 Jumper Cables, 16 Ft.

## SPECIFICATIONS:

### Model FAN8-12V Portable Ventilating Fan

Motor:	12 VDC
Blower Diameter:	8" (203mm)
Dimensions:	14"H x 12"W x 14"D (355mm x 305mm x 330mm)
Weight:	14 Lbs (6.3 kg)
Airflow:	862 cfm Straight Duct 665 cfm 1-90° Bend 565 cfm 2-90° Bends
Noise:	74 dB



### Model FAN-7004CL Canister Duct, 25 Ft.

Duct Length:	25 Ft. (7.6 m)
Duct Diameter:	8" (203mm)
Dimensions (Stowed):	36"L x 13"W x 13"H (914mm x 330mm x 330mm)
Weight:	25 Lbs (10.4 kg)



### PWR-3X12 Power Pack

Battery Type	12 V, VRLA, AGM
Battery Capacity	33 Ampere Hour
Weight	33 lbs (14.9 kg)
Envelope (LxWxH)	11.5" x 6.5" x 15.5" (343mm x 178mm x 368mm)

### BC-U1 Battery Charger

Input Line Voltage, Freq.	90-230 V AC (±10%), 50-60 Hz (±10%)
Output Charge Current	4 A Max. (± 5%)
Output Charge Voltage	14.8 ± .20 V DC
Weight	2.4 lbs (1.1 kg)
Envelope (LxWxH)	6.75" x 4.15" x 2.00" (172mm x 105mm x 51mm)



### EC4-16 Extension Cable

Length:	16 Ft. (4.9m)
Weight:	7 lbs (3.2 kg)



### JC4-16 Jumper Cables

Length:	16 Ft. (4.9m)
Weight:	7 lbs (3.2 kg)